

MSS.04.025.100/101



## KTM EXC Modelle

### Motorschutz Montagehinweise

Alle vom Motorrad gelösten Schrauben sind gemäß Herstellerangaben wieder zu montieren, oder mit von SW-MOTECH gelieferten Schrauben zu ersetzen. Falls nicht anderweitig definiert, diese Schrauben nach Tabelle anziehen.

M6	9,6 Nm
M8	23 Nm
M10	46 Nm

Gegebenenfalls Schrauben mit flüssiger Schraubensicherung einkleben.

Prüfen Sie nach 50 km alle Verbindungen auf festen Sitz.

SW-MOTECH GmbH & Co. KG  
Ernteweg 8/10  
35282 Rauschenberg  
Germany

Tel.: ++ 49 (0) 6425 820 280  
Fax: ++ 49 (0) 6425 820 281

[www.sw-motech.com](http://www.sw-motech.com)

### Skid Plate Mounting Instructions

SW-MOTECH products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. SW-MOTECH takes no responsibility for damages caused by improper installation.

All screws, bolts, and nuts, including all replacement hardware provided by SW-MOTECH, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

M6	9,6 Nm
M8	23 Nm
M10	46 Nm









All screws, bolts, and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Loctite") should be used to secure all screws, bolts, and nuts.

**WARNUNG / ATTENTION**

Achtung: Die Boden- und Schräglagenfreiheit kann bei Nutzung dieses Anbauteils eingeschränkt sein.

Attention: Cornering and ground clearance can be reduced by using this accessory.

1 Motorschutz Skid Plate  MSS.04.025.900/001 Anzahl/ Pcs. 1	5 Befestigungslasche Fixing Lug  MSS.04.025.002 Anzahl/ Pcs. 1
2 Sechskantschraube Hexagon Screw  M6 x 20 DIN 933 Anzahl/ Pcs. 2	6 Sechskantschraube Hexagon Screw  M6 x 16 DIN 933 Anzahl/ Pcs. 4
3 Unterlegscheibe Washer  A 6.4 DIN 9021 Anzahl/ Pcs. 2	7 Unterlegscheibe Washer  M 6,4 DIN 9021 Anzahl/ Pcs. 2
4 Gummidämpfer Vibration Damper  MSS.00.003.016 Anzahl/ Pcs. 2	8 Mutter, selbstsichernd Locking Nut  M 6 DIN 6927 Anzahl/ Pcs. 2

! Benutzen Sie Position 6 und 7 mit 8 auf der rechten Seite.  
Use position 6 and 7 with 8 on the right side.

